

# Wobbler® i-mini Wobbler

www.  
SENNINGER.  
com



## i-mini-Wobbler

Sprinkler Base Pressure-US	psi		Sprinkler Base Pressure-Metric	bar	
	20	25		1.38	1.72
<b>#5 Nozzle - Beige (5/64")</b>			<b>#5 Nozzle - Beige (1.98 mm)</b>		
Flow (gpm)	0.75	0.84	Flow (L/hr)	170	191
Diameter at 3.0 ft ht (ft)	30.0	31.0	Diameter at 0.91 m ht (m)	9.2	9.5
Diameter at 6.0 ft ht (ft)	32.0	32.5	Diameter at 1.83 m ht (m)	9.8	9.9
<b>#6 Nozzle - Gold (3/32")</b>			<b>#6 Nozzle - Gold (2.38 mm)</b>		
Flow (gpm)	1.10	1.25	Flow (L/hr)	250	284
Diameter at 3.0 ft ht (ft)	31.0	31.4	Diameter at 0.91 m ht (m)	9.5	9.6
Diameter at 6.0 ft ht (ft)	34.0	34.5	Diameter at 1.83 m ht (m)	10.4	10.5
<b>#7 Nozzle - Lime (7/64")</b>			<b>#7 Nozzle - Lime (2.78 mm)</b>		
Flow (gpm)	1.51	1.69	Flow (L/hr)	343	384
Diameter at 3.0 ft ht (ft)	31.0	32.0	Diameter at 0.91 m ht (m)	9.5	9.8
Diameter at 6.0 ft ht (ft)	35.0	35.5	Diameter at 1.83 m ht (m)	10.7	10.8
<b>#8 Nozzle - Lavender (1/8")</b>			<b>#8 Nozzle - Lavender (3.18 mm)</b>		
Flow (gpm)	1.95	2.18	Flow (L/hr)	443	495
Diameter at 3.0 ft ht (ft)	31.5	32.0	Diameter at 0.91 m ht (m)	9.6	9.8
Diameter at 6.0 ft ht (ft)	35.5	36.0	Diameter at 1.83 m ht (m)	10.8	11.0

*Sprinkler performance may vary with actual field conditions. Inverted model stream heights range from 0.5 to 1.5 ft (0.2 to 0.46 m) above nozzle based on pressure and nozzle size.*