

# BIG GUN® PERFORMANCE (U.S. UNITS)

Flow and diameter (feet) information at various pressures with different nozzle sizes. (See information at bottom of page 11.)

## 75 TAPER RING NOZZLE — 24° TRAJECTORY

PSI	0.4"		0.45"		0.5"		0.55"		0.6"		0.65"		0.7"		0.75"		0.8"	
	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.
25*	—	—	—	—	—	—	42	146	50	155	59	161	69	167	80	174	91	182
30*	—	—	—	—	37	158	45	158	55	165	64	172	75	182	87	187	99	192
35	—	—	32	154	40	164	49	172	59	178	69	191	81	196	93	202	106	208
40	27	149	35	160	43	171	52	180	63	190	74	198	87	204	98	213	112	221
45	29	155	37	167	46	180	56	189	67	198	79	206	91	214	104	223	118	230
50	30	161	39	174	48	186	59	195	70	203	83	212	95	220	109	230	123	237
55	32	165	41	179	50	193	62	203	74	213	87	221	100	230	115	239	130	247
60	33	169	42	184	53	198	64	208	77	220	91	228	104	237	120	245	136	254
65	35	172	44	189	55	205	67	216	80	227	95	237	109	247	125	254	142	263
70	36	175	45	194	57	210	69	221	83	232	98	243	113	254	129	260	147	270
75	37	179	47	201	59	217	72	228	86	239	101	250	117	261	134	268	153	277
80	39	182	49	207	61	222	74	234	89	244	105	256	121	266	138	274	158	283

\*Operating at pressures above 30 PSI provides better performance.

## 100 TAPER BORE NOZZLE — 24° TRAJECTORY


PSI	0.5"		0.55"		0.6"		0.65"		0.7"		0.75"		0.8"		0.85"		0.9"		1.0"	
	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.
40	47	191	57	202	66	213	78	222	91	230	103	240	118	250	134	256	152	262	—	—
50	50	205	64	215	74	225	87	235	100	245	115	256	130	265	150	273	165	280	204	300
60	55	215	69	227	81	240	96	250	110	260	126	270	143	280	164	288	182	295	224	316
70	60	225	75	238	88	250	103	263	120	275	136	283	155	295	177	302	197	310	243	338
80	64	235	79	248	94	260	110	273	128	285	146	295	165	305	189	314	210	325	258	354
90	68	245	83	258	100	270	117	283	135	295	155	306	175	315	201	326	223	335	274	362
100	72	255	87	268	106	280	123	293	143	305	163	316	185	325	212	336	235	345	289	372
110	76	265	92	278	111	290	129	303	150	315	171	324	195	335	222	344	247	355	304	380

## 150 TAPER BORE NOZZLE — 24° TRAJECTORY

PSI	0.7"		0.8"		0.9"		1.0"		1.1"		1.2"		1.3"		1.4"	
	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.
50	100	250	130	270	165	290	205	310	255	330	300	345	350	360	408	373
60	110	265	143	285	182	305	225	325	275	345	330	365	385	380	446	396
70	120	280	155	300	197	320	245	340	295	360	355	380	415	395	483	412
80	128	290	165	310	210	335	260	355	315	375	380	395	445	410	516	427
90	135	300	175	320	223	345	275	365	335	390	405	410	475	425	547	442
100	143	310	185	330	235	355	290	375	355	400	425	420	500	440	577	458
110	150	320	195	340	247	365	305	385	370	410	445	430	525	450	605	471
120	157	330	204	350	258	375	320	395	385	420	465	440	545	460	632	481

## 200 TAPER BORE NOZZLE — 27° TRAJECTORY

PSI	1.05"		1.1"		1.2"		1.3"		1.4"		1.5"		1.6"		1.75"		1.9"	
	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.	GPM	DIAM. FT.
60	250	345	285	355	330	375	385	390	445	410	515	430	585	445	695	470	825	495
70	270	360	310	380	355	395	415	410	480	430	555	450	630	465	755	495	890	515
80	290	375	330	395	380	410	445	430	515	450	590	470	675	485	805	515	950	535
90	310	390	350	410	405	425	475	445	545	465	625	485	715	505	855	535	1005	555
100	325	400	370	420	425	440	500	460	575	480	660	500	755	520	900	550	1060	575
110	340	410	390	430	445	450	525	470	605	495	695	515	790	535	945	565	1110	590
120	355	420	405	440	465	460	545	480	630	505	725	530	825	550	985	580	1160	605
130	370	425	425	445	485	465	565	485	655	515	755	540	860	560	1025	590	1210	620



See opposite page for nozzle descriptions.



# BIG GUN® PERFORMANCE (METRIC)

Flow and diameter (meters) information at various pressures with different nozzle sizes. (See information at bottom of page.)

## 75 TAPER RING NOZZLE TR75 — 24° TRAJECTORY

Kg/cm <sup>2</sup>	10.2 mm			11.4 mm			12.7 mm			14.0 mm			15.2 mm			16.5 mm			17.8 mm			19.1 mm			20.3 mm		
	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M
1.75*	—	—	—	—	—	—	—	—	—	2.64	9.5	44	3.17	11.4	48	3.72	13.4	49	4.30	15.5	51	4.91	17.7	54	5.59	20.1	56
2.00*	—	—	—	—	—	—	2.33	8.4	48	2.82	10.2	48	3.39	12.2	51	3.98	14.3	52	4.59	16.5	56	5.25	18.9	58	5.97	21.5	59
2.50	—	—	—	2.11	7.6	47	2.61	9.4	50	3.16	11.4	53	3.79	13.6	55	4.45	16.0	58	5.14	18.5	60	5.87	21.1	62	6.68	24.0	64
3.00	1.83	6.6	47	2.32	8.3	50	2.86	10.3	53	3.46	12.4	57	4.15	14.9	59	4.88	17.6	61	5.63	20.3	63	6.43	23.1	66	7.32	26.3	69
3.50	1.98	7.1	49	2.50	9.0	52	3.09	11.1	57	3.74	13.4	60	4.48	16.1	62	5.27	19.0	64	6.08	21.9	67	6.95	25.0	70	7.90	28.4	73
4.00	2.11	7.6	50	2.67	9.6	54	3.30	11.9	59	3.99	14.4	62	4.79	17.2	65	5.63	20.3	67	6.50	23.4	71	7.43	26.7	73	8.45	30.4	76
4.50	2.24	8.1	52	2.84	10.2	57	3.50	12.6	62	4.24	15.2	66	5.08	18.3	68	5.97	21.5	71	6.89	24.8	75	7.88	28.4	78	8.96	32.3	80
5.00	2.36	8.5	53	2.99	10.8	60	3.69	13.3	64	4.46	16.1	68	5.35	19.3	70	6.30	22.7	74	7.26	26.1	78	8.30	29.9	80	9.45	34.0	84
5.50	2.48	8.9	55	3.13	11.3	62	3.87	13.9	66	4.68	16.9	70	5.61	20.2	73	6.60	23.8	77	7.62	27.4	81	8.71	31.3	83	9.90	35.7	86
6.00	2.59	9.3	56	3.27	11.8	63	4.04	14.6	68	4.89	17.6	72	5.86	21.1	74	6.90	24.8	79	7.96	28.6	84	9.09	32.7	85	10.3	37.2	87

\*Operating at pressures above 2 Kg/cm<sup>2</sup> provides better performance.

## 100 TAPER BORE NOZZLE — 24° TRAJECTORY

Kg/cm <sup>2</sup>	12.7 mm			14.0 mm			15.2 mm			16.5 mm			17.8 mm			19.1mm			20.3 mm			21.6 mm			22.9 mm			25.4 mm		
	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M			
3.0	3.00	10.8	59.5	3.73	13.4	62.6	4.33	15.6	66.1	5.09	18.3	66.8	5.84	21.0	71.4	6.71	24.1	74.5	7.64	27.5	77.5	8.74	31.5	79.5	9.67	34.8	81.4	11.9	42.8	88.1
4.0	3.40	12.2	64.3	4.25	15.3	67.8	5.00	18.0	71.8	5.86	21.1	74.8	6.82	24.6	77.8	7.73	27.8	81.0	8.66	31.2	82.8	10.1	36.2	86.4	11.2	40.4	88.6	13.8	49.5	94.8
5.0	3.79	13.6	69.0	4.72	17.0	72.7	5.59	20.1	76.4	6.56	23.6	80.2	7.62	27.5	84.4	8.66	31.2	86.7	9.91	34.9	90.4	11.3	40.5	92.5	12.5	45.2	94.7	15.5	55.6	103
6.0	4.17	15.0	73.4	5.14	18.5	77.3	6.12	22.1	80.7	7.19	25.9	85.0	8.35	30.1	88.7	9.51	34.3	91.8	10.9	38.2	94.7	12.4	44.5	97.7	13.7	49.5	101	16.8	60.5	109
7.0	4.53	16.3	77.6	5.52	19.9	81.6	6.61	23.8	85.0	7.75	27.9	89.3	9.02	32.5	93.0	10.3	37.0	96.1	11.7	41.3	99.0	13.3	48.0	102.2	14.8	53.5	105	18.2	65.5	113
8.0	4.89	17.6	81.7	5.84	21.0	85.7	7.07	25.5	89.3	8.25	29.7	93.1	9.64	34.8	97.3	11.0	39.4	99.7	12.5	44.1	103	14.2	51.2	105.8	15.9	57.2	109	19.5	70.2	116

## 150 TAPER BORE NOZZLE — 24° TRAJECTORY

Kg/cm <sup>2</sup>	17.8 mm			20.3 mm			22.9 mm			25.4 mm			27.9 mm			30.5 mm			33.0 mm			35.6 mm		
	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M
3.5	6.39	23.0	76.0	8.29	29.8	82.0	10.5	37.8	88.0	13.0	46.9	95.0	15.9	57.1	101	19.0	68.3	105	22.3	80.1	110	25.8	92.9	114
4.0	6.83	24.6	79.6	8.86	31.9	85.6	11.2	40.4	91.6	13.9	50.1	97.8	16.9	61.0	104	20.3	73.0	109	23.8	85.7	114	27.4	98.6	118
5.0	7.63	27.5	85.4	9.91	35.7	91.6	12.6	45.2	98.6	15.6	56.0	105	18.9	68.2	111	22.7	81.7	117	26.6	95.8	121	30.8	111	126
6.0	8.36	30.1	89.7	10.9	39.1	96.7	13.8	49.5	104	17.0	61.3	110	20.8	74.7	117	24.9	89.5	123	29.1	105	128	33.6	121	133
7.0	9.03	32.5	95.0	11.7	42.2	101	14.9	53.5	108	18.4	66.3	114	22.4	80.7	122	26.8	96.6	128	31.5	113	134	36.4	131	139
8.0	9.66	34.8	99.3	12.5	45.1	105	15.9	57.2	112	19.7	70.8	118	24.0	86.3	126	28.7	103	132	33.7	121	138	38.9	140	145
9.0	10.2	36.9	104	13.3	47.9	110	16.8	60.6	117	20.9	75.1	123	25.4	91.5	131	30.4	110	137	35.7	129	143	41.1	148	149

## 200 TAPER BORE NOZZLE — 27° TRAJECTORY

Kg/cm <sup>2</sup>	26.7 mm			27.9 mm			30.5 mm			33.0 mm			35.6 mm			38.1 mm			40.6 mm			44.5 mm			48.3 mm		
	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M	L/S	M <sup>3</sup> /H	DIAM. M			
4.0	15.5	55.7	104	17.8	63.9	106	20.3	73.1	112	23.8	85.8	117	27.5	98.9	123	32.2	116	129	36.1	130	134	42.9	154	141	50.7	183	149
5.0	17.3	62.3	111	19.9	71.5	117	22.7	81.7	121	26.7	96.0	126	30.7	111	132	36.0	130	138	40.3	145	143	48.0	173	152	56.7	204	158
6.0	19.0	68.2	115	21.8	78.3	121	24.9	89.5	126	29.2	105	132	33.7	121	138	39.4	142	144	44.2	159	149	52.6	189	158	62.1	224	164
7.0	20.5	73.7	122	23.5	84.6	128	26.9	96.7	134	31.5	114	140	36.3	131	146	42.6	153	152	47.7	172	159	56.8	204	168	67.1	241	175
8.0	21.9	78.8	126	25.1	90.4	132	28.7	103	138	33.7	121	144	38.9	140	152	45.5	164	159	51.0	184	165	60.7	218	174	71.7	258	182
9.0	23.2	83.6	130	26.6	95.9	136	30.4	110	142	35.8	129	148	41.2	148	157	48.3	174	164	54.1	195	170	64.4	232	180	76.0	274	188

Diameters are based on a 24° trajectory for the 75, 100 and 150 Series and a 27° trajectory for the 200 Series. The lower trajectory angles result in better wind fighting ability, but reduced throw distances. Throw reduction depends upon nozzle flow rate. In general, the throw distance is reduced approximately 3% with each 3° drop in trajectory angle. Use of the wedge insert to modify trajectory will affect distance. Big Gun® performance data has been obtained under ideal test conditions and may be adversely affected by wind, poor hydraulic entrance conditions or other factors. Test riser height of 3 feet (0.91 meters) above measurement surface. No representation regarding droplet condition, uniformity, application rate, or suitability for a particular application is made herein.

Additional nozzle options and sizes available. Go to [www.nelsonirrigation.com](http://www.nelsonirrigation.com) or contact the factory for nozzle performance.

**TAPER BORE NOZZLE.** Most common nozzle type. Used where the available water flow and pressure are consistent. A nozzle size must be specified when ordering a Big Gun with a Taper Bore Nozzle. *The Nozzle Valve End Gun requires a Taper Bore Nozzle.*

**RING NOZZLE SET.** The Ring Nozzle Set is an easy and economic way of changing nozzles to match the available water flow and pressure. These are commonly used where the available water flow and pressure are variable and or when the Big Gun is shifted between various water sources with different capacities. The abrupt orifice of the nozzle is less efficient so the radius of throw is less than that achieved with an equivalent diameter Taper Bore nozzle. The abrupt orifice of the Ring Nozzle does break the stream of water up more, which can be an advantage in low pressure applications. The Ring Nozzle comes with a set of rings. *The Ring Nozzle should not be used with the Nozzle Valve End Gun.*

**TAPER RING NOZZLE.** This nozzle combines the changeability of a Ring Nozzle with some of the efficiency of a Taper Bore Nozzle. When ordering the Taper Ring Nozzle, specify the size as only one Taper Ring comes with the nozzle body and cap. Additional taper ring sizes can be purchased. *The Taper Ring Nozzle should not be used with the Nozzle Valve End Gun.*