

# mini-Wobbler Wobbler®

www.  
SENNINGER.  
com



## mini-Wobbler

### Sprinkler Base Pressure-US

	psi			Sprinkler Base Pressure-Metric	bar		
	15	20	25		1.03	1.38	1.72
<b>#4 Nozzle - Light Blue (1/16")</b>				<b>#4 Nozzle - Light Blue (1.59 mm)</b>			
Flow (gpm)	0.42	0.50	0.56	Flow (L/hr)	95	114	127
Diameter at 1.5 ft ht (ft)	26.5	28.0	29.0	Diameter at 0.46 m ht (m)	8.1	8.5	8.8
Diameter at 3.0 ft ht (ft)	31.0	32.0	33.0	Diameter at 0.91 m ht (m)	9.5	9.8	10.1
<b>#5 Nozzle - Beige (5/64")</b>				<b>#5 Nozzle - Beige (1.98 mm)</b>			
Flow (gpm)	0.64	0.75	0.84	Flow (L/hr)	145	170	191
Diameter at 1.5 ft ht (ft)	31.0	33.5	35.0	Diameter at 0.46 m ht (m)	9.5	10.2	10.7
Diameter at 3.0 ft ht (ft)	36.5	39.0	39.5	Diameter at 0.91 m ht (m)	11.1	11.9	12.0
<b>#6 Nozzle - Gold (3/32")</b>				<b>#6 Nozzle - Gold (2.38 mm)</b>			
Flow (gpm)	0.95	1.10	1.25	Flow (L/hr)	216	250	284
Diameter at 1.5 ft ht (ft)	33.0	36.0	37.0	Diameter at 0.46 m ht (m)	10.1	11.0	11.3
Diameter at 3.0 ft ht (ft)	39.5	42.0	42.0	Diameter at 0.91 m ht (m)	12.0	12.8	12.8
<b>#7 Nozzle - Lime (7/64")</b>				<b>#7 Nozzle - Lime (2.78 mm)</b>			
Flow (gpm)	1.30	1.51	1.69	Flow (L/hr)	295	343	384
Diameter at 1.5 ft ht (ft)	35.0	37.5	38.5	Diameter at 0.46 m ht (m)	10.7	11.4	11.7
Diameter at 3.0 ft ht (ft)	41.0	43.0	43.0	Diameter at 0.91 m ht (m)	12.5	13.1	13.1
<b>#8 Nozzle - Lavender (1/8")</b>				<b>#8 Nozzle - Lavender (3.18 mm)</b>			
Flow (gpm)	1.67	1.95	2.18	Flow (L/hr)	379	443	495
Diameter at 1.5 ft ht (ft)	35.5	38.5	39.0	Diameter at 0.46 m ht (m)	10.8	11.7	11.9
Diameter at 3.0 ft ht (ft)	41.5	43.0	43.5	Diameter at 0.91 m ht (m)	12.7	13.1	13.3

Also available with #9 and #10 nozzle. Consult factory for specific performance data.

Sprinkler performance may vary with actual field conditions. Upright model stream heights range from 1.5 to 3.0 ft (0.46 to 0.91 m) above the nozzle based on pressure and nozzle size. Minimum recommended riser height is 1.5 ft (0.46 m).